



## SLIDING AXLE TRAILER

[www.gincor.com](http://www.gincor.com)

### STANDARD FEATURES

- Length Overall: 48 Ft.
- Deck Width: 102"
- Capacity: 35 metric tons, main deck rating 50,000 Lbs. in 10'
- King Pin Set Back: 21"
- Coupler Height: 49"
- Upper Deck Height: 60" Approximate
- Upper Deck: 10' Length X 102" Width, 1 5/16" Apitong Decking.
- Lower Deck: 38' X 102" X 37" Height With 1 5/16" Apitong Decking. Front of deck lifts on 2-5" hydraulic cylinders at 2000 min to 3000 max psi to level with upper deck. Approach angle when lifted is approximately 6 1/2-8 degrees.



## CONSTRUCTION

Main beams fabricated in house of T-1 100,000 yield plate 16" main beams. Crossmembers are 3" I-beam. All side rails fabricated T-1 upper deck is T-1 and HSLA plate fabricated main beams, 12" depth with 8" channel crossmembers and 10" deep outside rail.

## SECUREMENT

Deck comes with chain keyhole slots every 2'.

## FIFTH WHEEL PLATE

3/8" HSLA plate with 2" Holland SAE pin.

## JACK

1pr. Holland mark v 2-speed, heavy duty.

## SUSPENSION

3 – Hendrickson HT250 series underslung 6.5" Ride height, 60" x 60"x 60" C/W dump valve & load gauge.

## AXLES

3 - 23,000lb. X 77 1/2"

## AXLE MOTION

Axles move on 4, 6" diameter rollers, powered by two 4" hydraulic cylinders. Sliding axle speed is controlled by output of truck hydraulic fluid and is measured in gallons per minute

## HUBS

15" – 8 bolt piloted.

## BRAKES

12.25 X 7.5 C/W 30/30 Maxis; auto slacks & dust shields.

## TIRES

12 – 235/75r17.5 Cooper Tires

## WHEELS:

12-steel 8 bolt 6.75 X 17.5.

## ABS

2SIM Haldex

## STORAGE

2 – aluminum box 12" x 24" x 36" upper deck each side.

## WINCH

2 speed 30,000 lbs. Warn winch, 245 feet of 5/8 cable.

## PAINT PROCESS

Mechanical clean, commercial sandblast, 2-part epoxy primer, polyurethane finish,

## COLOUR OPTIONS

John Deer Yellow  
Cardinal Red  
Omaha Orange  
Black

## HYDRAULICS

Wet line connection at front rail for tractor connection.

## HYD. CONTROL

Manual control roadside of goose neck remote control comes with, winch control, deck tilt, sliding axle

## ELECTRICAL

7-wire cable harness C/W 7 pin plug. Junction box front of trailer.

## LIGHTS

LED strobe lights rear facing deck work  
lights stop, turn and running lights  
side marker lights

## CONSPICUITY TAPE

All round to D.O.T. Standards.

## MUD FLAPS

1pr. behind fixed tridem

## DOCUMENTS

1- holder mounted in front of goose neck.

We've been building trailers for 40 years. Our longevity has been fueled by our ability to meet customers demands and to foster a great work environment for our people. Our customers trust us to solve their problems and deliver a premium product.

## GINCOR WERX

J.C. Trailers  
25975 Woodbine Avenue  
Keswick, ON  
L4P 3E9  
Phone: (905) 476-6572  
Fax: (905) 476-6751



J.C. Trailers is a member of the Gincor Werx group of companies.