

Our goal towards engineering a premium product and continuous improvement in our overall designs translate to a quality investment for our customers.

GINCOR Werx Live Bottom Trailers are designed by our engineers using their legacy of knowledge, and incorporating the latest technologies to manufacture a solid, reliable, durable product. Our reputation has been fueled by our ability to meet customer demands and deliver premium trailers.





STANDARD FEATURES

- Complete Hardox[™] 450 steel body
- 4" full-roller chain
- Standard reversible-direction belt
- Air ride suspension w/ 25,000 lb axle
- · Automatic chain oilers
- PPG™ Delfleet Essential primer & paint
- Full LED lighting
- 2-speed landing gear, Holland Mark V
- Black plastic half round rear fenders
- Aluminum light bars
- Fully insulated walls
- Manual slide tarp (front-back)
- Rear strobe lights
- Air operated tailgate

OPTIONS

- Calcium Sprayer
- Camera systems to monitor unloadinge
- Aluminum tailgate
- Auto-sensing lift axles
- Secondary gate locks
- Aluminum wheels
- Aluminum or stainless steel half round fenders
- Stainless steel outer sheeting
- Hendrickson Intraax Suspension
- Electric tarp
- · Back-up alarm, back-up lights
- Polished aluminum outer sheeting
- Various tarp options







Body	
1/8" 450 AR steel body	Standard
Stainless steel No 8 mirror finished exterior side wall sheeting	Optional
Aluminum mill finished exterior side wall sheeting	Optional
Premium Fiber Strand Moisture Resistant Insulation	Standard
Chain Inspection Doors on Each Side	Standard
Aluminum Ladder	Standard
Rear Shedder Plate	Standard
Frame	
Colour Black	Standard
Custom Colour	Optional
End Gate	
10 Gauge Mild Steel	Standard
Aluminum	Optional
Air Lift with manual switch in control box, electric wired to ISO	Standard
Air Lock with manual switch in control box, electric wired to ISO	Standard
Door Indicator - Easy View	Standard
Air Lubricator and Filter	Standard

Landing Gear	
2-speed landing gear with Gearbox on D/S 17" Travel	Standard
Structural Extruded Aluminum Tube Braces	Standard
Chain Drive / Belt	
Planetaries with Hydraulic Motors	Standard
Heat & Oil Resistant 2 Ply Belt	Standard
4" Pitch Roller Chain with 1" x 2" Cross Braces	Standard
Spring Loaded Belt Scraper	Standard
Forward/Reverse Hydraulic Manifold	Standard
Automatic Chain Oiler with Manual Adjustment/Shut Off	Standard
Primary Suspension	
Primary Suspension Air ride suspension w/ 25,000 lb axle	Standard
	Standard Optional
Air ride suspension w/ 25,000 lb axle	
Air ride suspension w/ 25,000 lb axle Axle chains to prevent bottom out	
Air ride suspension w/ 25,000 lb axle Axle chains to prevent bottom out Lift Steer/Axle and Suspension	Optional
Air ride suspension w/ 25,000 lb axle Axle chains to prevent bottom out Lift Steer/Axle and Suspension 25,000 lb steerable lift axle	Optional Standard
Air ride suspension w/ 25,000 lb axle Axle chains to prevent bottom out Lift Steer/Axle and Suspension 25,000 lb steerable lift axle UBL lift with manual control	Optional Standard
Air ride suspension w/ 25,000 lb axle Axle chains to prevent bottom out Lift Steer/Axle and Suspension 25,000 lb steerable lift axle UBL lift with manual control Fenders	Optional Standard Optional
Air ride suspension w/ 25,000 lb axle Axle chains to prevent bottom out Lift Steer/Axle and Suspension 25,000 lb steerable lift axle UBL lift with manual control Fenders Front - aluminum checker plate fenders	Optional Standard Optional Standard



Lighting & Electrical	
Full LED Lighting (3 Lights on top tube)	Standard
Strobe Lights in Rear Header-Pair	Standard
7 Wire ISO Plug To Rear Junction Box	Standard
Work Lights @ Rear-LED Wired To ISO	Standard
Release Agent System	
Aluminum Release Agent Tank & Spray	Optional
Hubs and Drums	
Unimount with Long Studs	Standard
Hubs filled with gear oil 80W-90 (steerable lift axle)	Standard
Tires	
22.5"	Optional
Outer Wheels & Inner Wheels	
White Steel	Optional
Flaps	
4@ rear (2 flip up) 2 in front of suspension, 2 behind front fenders	Standard
Tarp Options	
Electric slide tarp (front-back)	Standard
12" Hoops	Standard
Vinyl / mesh	Optional
Black	Standard
Custom colour	Optional

This literature is for illustrative purposes only. Some standard features and options may not be exactly as shown or reflective of your geographic region of operation. Consult your GINCOR Werx representative for details. Specifications are subject to change without notice.

GTW-393LBC-S 03/2025 NA

