GINCOR WERX STEP DECK - STANDARD FRAME

42' STEP DECK STANDARD FRAME

Length	Width	# of Axles	Rails	Webbing	Mid Ramp	Stake Pockets	Colour	Spacing	Landing Gear	Suspensions	Tires	Rims	Decking	Toolbox	Dunnage Rack	Winches	D-Rings	Ramps	Lighting	Options
42'	9'6	3	6"x1/2" Strenx	1/4"	5'	side only 24" Centers	Black	60"	LGS-3A105	HT250US.1, 16.5" Brakes, 89.5" track	255/70R22.5	22.5"x8.25" White Steel, 22.5"x8.25" Aluminum	1 5/16" Fir	1	-	17	-	Air Assist Angle Iron	Standard, strobes, Swing out wide load lights	-

45' STEP DECK STANDARD FRAME

Length	Width	# of Axles	Rails	Webbing	Mid Ramp	Stake Pockets	Colour	Spacing	Landing Gear	Suspensions	Tires	Rims	Decking	Toolbox	Dunnage Rack	Winches	D-Rings	Ramps	Lighting	Options
45'	9'6	2	6"x1/2" Strenx	1/4"	5'	4xfront, sides 24" centers	Galvanized	49"	LGS-3A105	HT250US.1, 16.5" Brakes, 77.5" track	235/75R17.5	17.5"x6.75" Aluminum	1 5/16" Apitong	1	1	20	-	Spring Assist Angle Iron	Standard, strobes, 7 way plug	-

46' STEP DECK STANDARD FRAME

Length	Width	# of Axles	Rails	Webbing	Mid Ramp	Stake Pockets	Colour	Spacing	Landing Gear	Suspensions	Tires	Rims	Decking	Toolbox	Dunnage Rack	Winches	D-Rings	Ramps	Lighting	Options
46'	9'6	3	5"x1/2" Strenx	1/4", 3/16"	5'	side only 24" Centers	Black	60"	LGS-3A105	HT250US.1, 16.5" Brakes, 89.5" track	255/70R22.5	22.5"x8.25"White Steel, 22.5"x8.25" Aluminum	1 5/16" Fir	1	-	17	-	Air Assist Angle Iron	Standard, strobes, Swing out wide load lights	-

48' STEP DECK STANDARD FRAME

Length	Width	# of Axles	Rails	Webbing	Mid Ramp	Stake Pockets	Colour	Spacing	Landing Gear	Suspensions	Tires	Rims	Decking	Toolbox	Dunnage Rack	Winches	D-Rings	Ramps	Lighting	Options
48'	9'6	3	6"x1/2" Strenx	1/4"	5'	side only 24" Centers	Black	60"	LGS-3A105	HT250US.1, 16.5" Brakes, 77.5" track	255/70R22.5	22.5"x8.25"White Steel, 22.5"x8.25" Aluminum	1 5/16" Fir	2	-	12	16	Air Assist Angle Iron	Standard, strobes, Swing out wide load lights	Prep for winch

GINCOR WERX STEP DECK - STANDARD FRAME

53' FLATBED STANDARD FRAME

Length	Width	# of Axles	Rails	Webbing	Mid Ramp	Stake Pockets	Colour	Spacing	Landing Gear	Suspensions	UBL	Tires	Rims	Decking	Toolbox	Winches Track	Winches	D-Rings	Ramps	Lighting	Options
53'	9'6	3	6"x1/2" Strenx	1/4", 3/16"	5'		Black	60"	LGS-3A105	HT250US.1, 16.5" Brakes, 83.5" track		255/70R22.5	22.5"x8.25"White Steel, 22.5"x8.25" Aluminum	1 5/16" Fir	1		11	16	Air Assist Angle Iron	Standard, strobes, Swing out wide load lights	Prep for winch
53'	8'6	3	5"x3/8" Strenx/ 5"x1/2"	1/4", 3/16"		4xfront, sides 24" centers	Black	60"	LGS-3A105	HT250US.1, 16.5" Brakes, 77.5" track		255/70R22.5	22.5"x8.25"White Steel, 22.5"x8.25" Aluminum	1 5/16" Fir	1		22		Spring Assist Angle Iron. Middle Ramp Spring Assist Angle Iron	Standard, strobes, Swing out wide load lights, 4 way plug	
53'	8'6	3	5"x3/8" Strenx	1/4", 3/16"		side only 24" Centers	Black	60"	LGS-3A105	HT250US.1, 16.5" Brakes, 77.5" track		255/70R22.5	22.5"x8.25"White Steel	1 5/16" Fir						Standard	
53'	8'6	3	5"x3/8" Strenx	1/4", 3/16"		side only 24" Centers	Galvanized	72"	LGS-3A105	HT250US.1, 16.5" Brakes, 77.5" track		255/70R22.5	22.5"x8.25"White Steel	1 5/16" Apitong	1	C-Channel - Driver Side	22		Air Assist Bi-Fold Wood Filled	Standard, strobes	Bolt-On Traction Bars, Chain Box, Toolbox above 5th Wheel & top of Rear Deck
53'	8'6	3	5"x3/8" Strenx	1/4", 3/16"		side only 24" Centers	Galvanized	72"	LGS-3A105	HT250US.1, 16.5" Brakes, 77.5" track	Front Axle	235/75R17.5	17.5"x 6.75" White Steel, 17.5"x6.75" Aluminum	1 5/16" Apitong	1	C-Channel - Driver Side	18		Air Assist Bi-Fold Wood Filled	Standard, strobes	Bolt-On Traction Bars, Chain Box, Toolbox above 5th Wheel & top of Rear Deck
53'	8'6	3	5"x3/8" Strenx	1/4", 3/16"		side only 24" Centers	Galvanized	72"	LGS-3A105	HT250US.1,16.5" Brakes,77.5" track		235/75R17.5	17.5"x 6.75" Galvanized	1 5/16" Apitong		Double L			Air Assist Bi-Fold Wood Filled	Standard	
53'	8'6	3	5"x3/8" Strenx	1/4", 3/16"		side only 24" Centers	Galvanized	72"	LGS-3A105	HT250US.1, 16.5" Brakes, 77.5" track		235/75R17.5	17.5"x 6.75" Galvanized	1 5/16" Apitong		Double L			Manual Spring Assist Angle Iron	Standard	
53'	8'6	3	5"x3/8" Strenx	1/4", 3/16"		side only 24" Centers	Galvanized	72"	LGS-3A105	HT250US.1, 16.5" Brakes, 77.5" track		235/75R17.5	17.5"x 6.75" Galvanized	1 5/16" Apitong		Double L			Air Assist Wood Filled	Standard	

55' STEP DECK STANDARD FRAME

Length	Width	# of Axles	Rails	Webbing	Mid Ramp	Stake Pockets	Colour	Spacing	Landing Gear	Suspensions	Tires	Rims	Decking	Toolbox	Dunnage Rack	Winches	D-Rings	Ramps	Lighting	Options
55'	9'6	3	6"x 5/8" Strenx	1/4"	-	side only 24" Centers	Black	60"	LGS-3A105	HT250US.1, 16.5" Brakes, 77.5" track	255/70R22.5	22.5"x8.25"White Steel, 22.5"x8.25" Aluminum	1 5/16" Fir	2	-	22	-	Spring Assist Angle Iron	Standard	-